

Page 2, line 23, delete "(to be inserted when ascertained)" and insert therefore -- March 27, 1997--.

Page 6, line 18, delete "(to be inserted when ascertained)," and insert therefore - -08/833,015,--.

Page 6, line 19, delete "(to be inserted when ascertained)," and insert therefore - -6562,--.

Page 6, lines 19 and 20, delete "(to be inserted when ascertained)" and insert therefore --March 27, 1997--.

Page 7, line 19, replace "Velcro" with --VELCRO--.

Page 8, line 31, replace "aperture 41" with---aperture 44--.

Page 9, line 28, replace "aperture 41" with 0--aperture 44--.

Page 9, line 33, replace "FIG. 7A" with --FIG. 8--.

Page 10, line 1, replace "periphery 55" with --periphery 57--.

Page 10, line 2, replace "FIG. 7A" with --FIG. 8--.

Page 15, line 31, replace "FIG. 14" with --FIGS. 2 and 4--.

Page 25, line 12, replace "52" with --51--.

IN THE DRAWINGS:

Please substitute the attached pages 3/12, 5/12, 6/12, 8/12, 10/12, 11/12, and 12/12 for those originally filed.

FIG. 5 has been amended to insert the reference numeral 44 with a line drawn to the aperture formed from the discontinuity in the backsheet 62. FIG. 7 has been amended to replace reference numeral 41 with 44. FIG. 8 has been amended to replace reference numeral 55 with 42. FIG. 10 has been amended to replace both occurrences of the reference number 55 with 57. FIGS. 14 and 15 have been amended to move the circle which represents cutting roller 152 down so that it is approximately located to the material on the conveyor belt. FIG. 16 has been amended by adding the term "FIG. 16". A red ink sketch of the drawing changes is provided for the Examiner's convenience.